

## **Building Specification Sheet for Armourcoat Pitted Finish with Paste Fill BSS19**

<b>Product:</b>	ARMOURCOAT Polished Plaster
<b>Manufacturer:</b>	Armourcoat Ltd. Morewood Close, London Road, Sevenoaks, Kent. TN13 2HU web: <a href="http://www.armourcoat.com">www.armourcoat.com</a>
<b>Location:</b>	(e.g. Walls and ceilings in retail area)
<b>Drawings:</b>	Refer to drawings no. ....
<b>Background:</b>	Substrate to be prepared in accordance with Armourcoat Ltd's guidance: <ul style="list-style-type: none"><li>• Plasterboard/Drylining Installation and Finishing (SSS1)</li><li>• Brick, Block and Concrete (SSS3)</li><li>• Glasroc and GRG (SSS4)</li><li>• Previously Decorated (SSS5)</li></ul>
<b>Preparation:</b>	Ensure a true, flat and even surface with wall surfaces that are constructed in accordance with specialist's requirements. Substrates must be free of curing compounds, dust, and other impurities such as oil, grease and salts.
<b>Primer:</b>	For surfaces with uneven suction apply Armourcoat K40 Primer in accordance with manufacturer's recommendations.
<b>Keycoat:</b>	Mix and apply Armourcoat Keycoat (K124 or K149) in accordance with manufacturer's working instructions.
<b>Finish:</b>	Apply Armourcoat Polished Plaster (PT P30 Y0183 CW) in accordance with manufacturer's working instructions. On the same day, trowel apply 1 thin coat of Armourcoat pre-mixed plaster (P80 N0145) into the semi-damp pitted finish. Allow to dry.
<b>Thickness:</b>	approx 2.0 mm – 2.5 mm
<b>Colour:</b>	Armourcoat ref: Pitted P30 Y0183 CW with Paste Fill P80 N0145 (Contact Armourcoat UK for method statement where necessary)
<b>Waxing:</b>	As required. Leave to dry completely before waxing. Supply and apply Armourcoat wax polish (Ref. White wax) in accordance with manufacturer's working instructions. Refer to Clause 250 in General Requirements.
<b>Samples:</b>	Control sample to be made by local agent for approval. Control sample to be retained onsite for referral by local Armourcoat agent.
<b>Application:</b>	The system is to be supplied and applied by Armourcoat Surface Finishes or an approved overseas agent. UK Contact: <span style="float: right;">Tel: 00 44 (0)1732 467993.</span>

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.  
SPD BSS19 1107©

**Armourcoat Limited**  
Morewood Close London Road  
Sevenoaks Kent TN13 2HU United Kingdom  
Tel: +44 (0)1732 460 668 Fax +44 (0)1732 450 930  
Email: [technical@armourcoat.co.uk](mailto:technical@armourcoat.co.uk)

**web: [www.armourcoat.com](http://www.armourcoat.com)**