

Product Data Sheet 15

Polished Plaster Colourwash

1 Product Description

Polished Plaster Colourwash is a water-based modified vegetable oil coating, used to overcoat Armourcoat Polished Plasters. The colourwash is absorbed slightly into the surface in varying amounts, depending on the surface compaction, enhancing tonal variation and depth of colour.

Polished Plaster Colourwash contains a refined vegetable oil that is derived from a renewable and sustainable resource.

2 Properties

- Quick and easy to apply, economically priced.
- Water-based product allowing for easy cleanup of site as well as application tools.
- Supplied ready for use on site.
- Tinted to a large range of standard and bespoke colours.
- Can be buffed to enhance the surface sheen.

3 Health And Safety

Polished Plaster Colourwash is water-based product. Good working practices should be followed when using the product. Protective clothing should be worn and ingestion and prolonged skin contact should be avoided. If contact with skin occurs, wash immediately with soap and water.

4 Suitable Substrates

Polished Plaster Colourwash is suitable to be applied over most Armourcoat Polished Plasters, which have been allowed to dry for at least 24 hours under good drying conditions.

5 Applying Polished Plaster Colourwash

Allow Polished Plaster to dry for at least 24 hours in good drying conditions. Shake the colourwash thoroughly prior to use.

The colourwash can be applied sponge float, acrylic decorators sponge or a lint free cotton cloth.

The Colourwash should be applied in a circular motion to a few square metres at a time. Once applied to a small area the surface is rubbed again with the sponge float or cloth to remove any swirl lines and even out the surface. If there is too much Colourwash on the surface, wipe over with a dry cloth to remove any excess and rub once again to achieve a consistent surface finish without swirl lines.

After the Colourwash has dried for at least an hour it can be buffed to a polish.

* Please note

Good drying conditions referred to means good ventilation **and** air circulation. Using fans, even in warm conditions, will greatly accelerate hardening. In very damp or humid conditions, it will also help to use a de-humidifier. If heat is used, it should not be directed at the finish and must not be damp heat as is created by gas burners.

6 Coverage Rates

Coverage rate approximately 15-20 m²/kg
One unit (800 g) will cover approximately 12 –15 m²
(120 -150 sq feet)

7 Storage

Store in dry conditions between 5 – 25⁰C. Protect from frost. Protect from sunlight and sources of direct heat. Keep container sealed when not in use.

Shelf life of Polished Plaster Colourwash in unopened container under correct storage conditions is 6 months from date of manufacture.

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.

SAT PDS15 0105©

Armourcoat Limited
Morewood Close London Road
Sevenoaks Kent TN13 2HU United Kingdom
Tel: +44 (0)1732 460 668 Fax +44 (0)1732 450 930
Email: technical@armourcoat.co.uk

web: www.armourcoat.com