



**Document: 8992.13**  
 Collection: 106: Product Data Sheets (PDS)  
 Modified: 15/02/2017 17:28  
 Created: 30/03/2016 17:31

**Armourcoat Ltd**  
 Morewood Close Sevenoaks Kent TN13 2HU  
 T: +44(0)1732 460 668 F: +44(0)1732 450 930  
 UK Company 1997888. VAT Reg: 445788013  
 www.armourcoat.com

# Product Data Sheet PDS020: Clearseal Gloss

For use with Armourcoat wall coatings

## 1 Product Description

Armourcoat Clearseal Gloss is a transparent, water based Polyurethane/Acrylic coating. It improves the physical properties of Armourcoat wall coatings by making it more durable and improving stain and abrasion resistance.

## 2 Properties

- enhances the physical properties of Armourcoat wall coatings
- quick and easy to apply and economically priced
- non-toxic water-based product
- supplied ready for use on site
- imparts improved stain resistance and cleanability
- viscosity - approx. 2000cPs
- dry solids - approx. 20%.

## 3 Health and Safety

Armourcoat Clearseal Gloss is a non-toxic, water-based product. Ensure good ventilation during application and drying. Avoid contact with skin and eyes. Keep out of reach of children.

## 4 Suitable Substrate

Armourcoat Clearseal Gloss is suitable to be applied over Armourcoat wall coatings (not including lime based products), which have been allowed to dry for at least 24 hours under good drying conditions\*.

**\* Please note:** Good drying conditions referred to means good ventilation **and** air circulation. Using fans, even in warm conditions, will greatly accelerate hardening. In very damp or humid conditions, it will also help to use a de-humidifier. If heat is used, it should not be directed at the finish and must not be damp heat as is created by gas burners.

## 5 Applying Clearseal Gloss

Using a short pile roller, roll on the Clearseal Gloss evenly across the wall. Work methodically so that no areas are missed and check carefully that there are no drips or tram lines left which may stay visible on the final finish. Roll on in one direction and then roll across at 90 to create an even coating.

## 6 Coverage Rates

Coverage rate approximately 12-16 m/lt. One unit will cover approximately 70 m (700 sq feet).

## 7 Storage

Store in dry conditions between 5°C - 25°C . Protect from frost. Protect from sunlight and sources of direct heat. Keep container sealed when not in use. Shelf life of Armourcoat Clearseal Gloss in unopened container under correct storage conditions is 18 months from date of manufacture.

---

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.