

ARMOURCOAT®

SUSTAINABLE LUXURY FINISHES

SPECIFICATION SHEET

DECORATIVE PAINT - TACTITE



An aesthetic water-based decorative wall coating creating a tough, durable and hygienic finish.

A high performance solution for demanding interiors, Tactite creates a tough, durable and hygienic wall coating. The finish is exceptionally hardwearing and easy to clean, making it highly suitable for commercial interiors such as hospitals, schools, offices and high traffic public areas where cleanliness is essential. Also ideal for domestic use, Tactite features a 'soft touch' feel to create a warm, inviting interior with a suede or textured finish.



MOULD
AND MILDEW
RESISTANT



SCRUB
RESISTANT



FIRE RATED





SPECIFICATIONS

DECORATIVE PAINT - TACTITE

| | |
|--|---|
| DESCRIPTION: | Armourcoat Tactite Decorative Paint |
| MANUFACTURER: | Armourcoat Ltd |
| CONTACT DETAILS: | Address: Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU Telephone: +44 (0)1732 460668 Web: www.armourcoat.com Email: specsales@armourcoat.co.uk |
| COMPONENTS: | Water-based polymer modified paint |
| FIRE RATING: | ASTM E84: Flame Spread index: 5, Smoke Development Index: 5, Classification: A |
| VOC CONTENT: | French VOC Label: A+, French CMR Components: Pass, Italian CAM Edilizia: Pass, ISO 11890-2: 5.5 |
| LOCATION: | As drawing |
| SYSTEM WEIGHT: | 0.36-0.42 kg/m ² |
| EMBODIED CARBON: | EN15804 +A2: 1.77 Kg CO ₂ e |
| TECHNICAL CHARACTERISTICS, OTHER: | Mould and mildew resistance, ASTM D3273 & ASTM D3274: 10/10/10, ASTM D2486, 1,150 to 1,925 cycles, ISO 2812: Class 2, ASTM D1308 |
| COLOUR: | Insert colour selection |
| SEALER: | Not required OR AquaWax optional |