

# ARMOURCOAT®

SUSTAINABLE LUXURY FINISHES

SPECIFICATION SHEET

## POLISHED PLASTER SELECTOR RANGE - SMOOTH (INTERNAL)



A luxurious finish with a natural stone look for interior and exterior use.

Smooth is natural, mid-sheen finish with visible crushed marble and light burnishing from the trowel application. The Smooth polished plaster finish is similar to the marmorino stucco, used extensively in northern Italy during the Renaissance period as an internal and external wall finish and as a background for the ornate frescoes which dominated much of the decoration of that time.



SUSTAINABLE  
ACCREDITATIONS



ZERO VOC



FIRE  
RATED



SPECIFICATIONS

# POLISHED PLASTER SELECTOR RANGE - SMOOTH (INTERNAL)

<b>DESCRIPTION:</b>	Armourcoat Smooth Polished Plaster Selector Range
<b>MANUFACTURER:</b>	Armourcoat Ltd
<b>CONTACT DETAILS:</b>	<p><b>Address:</b> Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU</p> <p><b>Telephone:</b> +44 (0)1732 460668</p> <p><b>Web:</b> <a href="http://www.armourcoat.com">www.armourcoat.com</a></p> <p><b>Email:</b> <a href="mailto:specsales@armourcoat.co.uk">specsales@armourcoat.co.uk</a></p>
<b>COMPONENTS:</b>	Natural lime and marble
<b>REACTION TO FIRE:</b>	EN 13501-1:2018: A2-s1,d0
<b>FIRE RATING:</b>	ASTM E84: Flame Spread index: 10, Smoke Development Index: 10, Classification: 1
<b>VOC CONTENT AND EMISSIONS:</b>	BBREEAM International v2.0 (2016): Exemplary Level, French VOC Label: A+, Indoor Air Comfort: Pass, ABG/AgBB: Pass, Belgian Regulation: Pass, ASTM D2369: <1, SCAQMD Rule 1113: Pass, LEED v4 + v4.1 BETA: Pass
<b>PREPARATORY REINFORCING SKIMCOAT:</b>	Armourcoat Anticrack OR not required
<b>LOCATION:</b>	As drawing
<b>HARDNESS:</b>	Shore D Hardness test: 64, ASTM D3363 Pencil Harness: 5H+
<b>RECYCLED CONTENT (MINIMUM):</b>	29%
<b>SYSTEM WEIGHT:</b>	2.40-3.0 kg/m <sup>2</sup>
<b>EMBODIED CARBON:</b>	EN15804 +A2: 0.34 Kg CO <sub>2</sub> e
<b>TECHNICAL CHARACTERISTICS, OTHER:</b>	Mould and mildew resistance, to ASTM D3274: 10/10/10
<b>COLOUR:</b>	Insert colour selection
<b>SEALER:</b>	Aquawax as standard