

SPECIFICATION SHEET

## POLISHED PLASTER SELECTOR RANGE - SPATULATA



A classically luxurious marble stucco plaster finish.

Spatulata is a superfine, high gloss finish with a non-directional pattern. Made from aged lime putty and crushed marble, the remarkable depth and sheen of the finish is achieved through the craftsmanship of the applicator. Spatulata is applied in numerous fine layers and trowel polished to a glassy surface, highlighting the inherent movement created by the traditional application technique.



SUSTAINABLE  
ACCREDITATIONS



NATURAL  
MATERIAL



FIRE RATED



SPECIFICATIONS

# POLISHED PLASTER SELECTOR RANGE - SPATULATA

<b>DESCRIPTION:</b>	Armourcoat Spatulata Polished Plaster Selector Range
<b>MANUFACTURER:</b>	Armourcoat Ltd
<b>CONTACT DETAILS:</b>	<p><b>Address:</b> Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU</p> <p><b>Telephone:</b> +44 (0)1732 460668</p> <p><b>Web:</b> <a href="http://www.armourcoat.com">www.armourcoat.com</a></p> <p><b>Email:</b> <a href="mailto:specsales@armourcoat.co.uk">specsales@armourcoat.co.uk</a></p>
<b>COMPONENTS:</b>	Natural lime and marble
<b>REACTION TO FIRE:</b>	EN 13501-1:2018: A2-s1,d0
<b>FIRE RATING:</b>	ASTM E84: Flame Spread index: 5, Smoke Development Index: 10, Classification: 1
<b>VOC CONTENT AND EMISSIONS:</b>	BREEAM International v2.0 (2016): Exemplary Level, French VOC Label: A+, ASTM D2369: <1, Indoor Air Comfort Gold: Pass, LEED v4 + v4.1 BETA: PASS, ABG/AgBB: Pass, Belgian Regulation: Pass, EMICODE: EC 1 Plus
<b>PREPARATORY REINFORCING SKIMCOAT:</b>	Armourcoat Anticrack OR not required
<b>LOCATION:</b>	As drawing
<b>HARDNESS:</b>	Shore D Hardness test: 74
<b>RECYCLED CONTENT (MINIMUM):</b>	0-59%
<b>SYSTEM WEIGHT:</b>	0.90-1.14 kg/m <sup>2</sup>
<b>EMBODIED CARBON:</b>	EN15804 +A2: 0.336 Kg CO <sub>2</sub> e
<b>TECHNICAL CHARACTERISTICS, OTHER:</b>	Mould and mildew resistance, to ASTM D3274: 10/10/10
<b>COLOUR:</b>	Insert colour selection
<b>SEALER:</b>	Eco Wax as standard