

ARMOURCOAT®

SUSTAINABLE LUXURY FINISHES

SPECIFICATION SHEET

POLISHED PLASTER SELECTOR RANGE - STRIATED



An elegant polished plaster inspired by raw silk.

Striated is a superfine wall finish with smooth horizontal striations created by the skilful hand application. Made from aged lime putty and recycled crushed marble, the natural mineral material is applied in multiple layers before the finish coat is lightly trowel polished. This final polish gives the subtle tonal variation that brings out the refined horizontal movement and creates the silk-like texture.



SUSTAINABLE
ACCREDITATIONS



NATURAL
MATERIAL



FIRE RATED





SPECIFICATIONS

POLISHED PLASTER SELECTOR RANGE - STRIATED

DESCRIPTION:	Armourcoat Striated Polished Plaster Selector Range
MANUFACTURER:	Armourcoat Ltd
CONTACT DETAILS:	Address: Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU Telephone: +44 (0)1732 460668 Web: www.armourcoat.com Email: specsales@armourcoat.co.uk
COMPONENTS:	Natural lime and marble
REACTION TO FIRE:	EN 13501-1:2018: A2-s1,d0
FIRE RATING:	ASTM E84: Flame Spread index: 5, Smoke Development Index: 10, Classification: 1
VOC CONTENT AND EMISSIONS:	BREEAM International v2.0 (2016): Exemplary Level, French VOC Label: A+, ASTM D2369: <1, Indoor Air Comfort Gold: Pass, LEED v4 + v4.1 BETA: PASS, ABG/AgBB: Pass, Belgian Regulation: Pass, EMICODE: EC 1 Plus
PREPARATORY REINFORCING SKIMCOAT:	Armourcoat Anticrack OR not required
LOCATION:	As drawing
HARDNESS:	Shore D Hardness test: 74
RECYCLED CONTENT (MINIMUM):	0-62%
SYSTEM WEIGHT:	0.90-1.14 kg/m ²
EMBODIED CARBON:	EN15804 +A2: 0.336 Kg CO ₂ e
TECHNICAL CHARACTERISTICS, OTHER:	Mould and mildew resistance, to ASTM D3274: 10/10/10
COLOUR:	Insert colour selection
SEALER:	Eco Wax as standard