

SPECIFICATION SHEET

SCULPTURAL PLASTER - AESIS



A calm three dimensional wall finish with gentle movement.

Aesis uses organic scalloped surfaces and free flowing plateaus to capture the calming movement often found in nature. A gentle design, Aesis brings a relaxed energy to interior spaces. The recommended finish for Aesis is Spatulata, a highly polished, superfine marble stucco polished plaster with amazing lustre.

Armourcoat Sculptural designs are handmade and seamlessly installed by skilled applicators before being decorated in the surface finish of your choice. Suitable for projects of all types, including swimming pools, sculptural designs are extremely durable and VOC free.







ACCREDITATIONS



FIRE RATED



SPECIFICATIONS

SCULPTURAL PLASTER - AESIS

DESCRIPTION:	Armourcoat Sculptural Plaster - Aesis
MANUFACTURER:	Armourcoat Ltd
CONTACT DETAILS:	Address: Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU Telephone: +44 (0)1732 460668 Web: www.armourcoat.com Email: specsales@armourcoat.co.uk
COMPONENTS:	Glass Reinforced Gypsum (GRG)
FIRE RATING:	EN 13501-1:2018: A1/A1 _{fl}
VOC CONTENT:	BREEAM International v2.0 (2016): Exemplary Level, BREEAM NOR v6 (2022): Exemplary Level, LEED v4 Beta (Feb 2021): Pass, French VOC Label: A+, French CMR Components: Pass, Italian CAM Edilizia: Pass, Indoor Air Comfort Gold: Pass, ABG/AgBB: Pass, Belgian Regulation: Pass
LOCATION:	As drawing
RECYCLED CONTENT (MINIMUM):	17%
DESIGN:	Aesis
FINISHES:	Matt emulsion paint OR Perlata OR Spatulata OR Armuralia
COLOUR:	Insert selection from finish colour palette
SEALER:	Defined by selected finish
SYSTEM WEIGHT:	18.0 kg/m²
THICKNESS:	20mm
EMBODIED CARBON:	EN15804 +A2: 0.082 Kg CO ₂ e
TECHNICAL CHARACTERISTICS, OTHER:	Mould and mildew resistance, ASTM C109M: =>33Mpa, ASTM C-348: =>10Mpa