

SPECIFICATION SHEET

## SCULPTURAL PLASTER - VAPOUR



## A calming three dimensional wall finish with flowing horizontal movement.

Vapour captures the essence of early morning mist on the water, using softly flowing surfaces with playful horizontal energy to create a refined and engaging wall surface. The recommended finish for Vapour is Perlata, a pearlescent decorative paint with a subtle shimmer and high durability.

Armourcoat Sculptural designs are handmade and seamlessly installed by skilled applicators before being decorated in the surface finish of your choice. Suitable for projects of all types, including swimming pools, sculptural designs are extremely durable and VOC free.







SUSTAINABLE



FIRE RATED





## **SPECIFICATIONS**

## SCULPTURAL PLASTER - VAPOUR

DESCRIPTION:	Armourcoat Sculptural Plaster - Vapour
MANUFACTURER:	Armourcoat Ltd
CONTACT DETAILS:	Address: Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU Telephone: +44 (0)1732 460668
	Web: www.armourcoat.com
	Email: specsales@armourcoat.co.uk
COMPONENTS:	Glass Reinforced Gypsum (GRG)
FIRE RATING:	EN 13501-1:2018: A1/A1 <sub>fl</sub>
VOC CONTENT:	BREEAM International v2.0 (2016): Exemplary Level, BREEAM NOR v6 (2022): Exemplary Level, LEED v4 Beta (Feb 2021): Pass, French VOC Label: A+, French CMR Components: Pass, Italian CAM Edilizia: Pass, Indoor Air Comfort Gold: Pass, ABG/AgBB: Pass, Belgian Regulation: Pass
LOCATION:	As drawing
RECYCLED CONTENT (MINIMUM):	17%
DESIGN:	Vapour
FINISHES:	Matt emulsion paint OR Perlata
COLOUR:	Insert selection from finish colour palette
SEALER:	Defined by selected finish
SYSTEM WEIGHT:	25.0 kg/m²
THICKNESS:	20mm
EMBODIED CARBON:	EN15804 +A2: 0.082 Kg CO <sub>2</sub> e
TECHNICAL CHARACTERISTICS, OTHER:	Mould and mildew resistance, ASTM C109M: =>33Mpa, ASTM C-348: =>10Mpa