

ARMOURCOAT®

SUSTAINABLE LUXURY FINISHES

SPECIFICATION SHEET

POLISHED PLASTER SELECTOR RANGE - KONCRETE (TEXTURED)



A raw finish with a refined,
urban character.

Koncrete Textured is coarse finish with a tactile, lightly polished surface. Inspired the brutalist aesthetic of poured concrete architecture, this polished plaster stays true to the raw material feel whilst introducing a sense of refinement and luxury. Crafted from hydrated lime and crushed recycled marble, the textured finish adds a modern, urban edge to interior spaces.



SUSTAINABLE
ACCREDITATIONS



ZERO VOC



FIRE
RATED



SPECIFICATIONS

POLISHED PLASTER SELECTOR RANGE - KONCRETE (TEXTURED)

DESCRIPTION:	Armourcoat Koncrete (Textured) Polished Plaster Selector Range
MANUFACTURER:	Armourcoat Ltd
CONTACT DETAILS:	<p>Address: Morewood Close, Sevenoaks, Kent, United Kingdom, TN13 2HU</p> <p>Telephone: +44 (0)1732 460668</p> <p>Web: www.armourcoat.com</p> <p>Email: specsales@armourcoat.co.uk</p>
COMPONENTS:	Natural lime and marble
REACTION TO FIRE:	EN 13501-1:2018: A2-s1,d0
FIRE RATING:	ASTM E84: Flame Spread index: 10, Smoke Development Index: 10, Classification: 1
VOC CONTENT AND EMISSIONS:	BREEAM International v2.0 (2016): Exemplary Level, French VOC Label: A+, Indoor Air Comfort: Pass, Indoor Air Comfort Gold: Pass, ABG/AgBB: Pass, Belgian Regulation: Pass, ASTM D2369: <1, SCAQMD Rule 1113: Pass, LEED v4 + v4.1 BETA: Pass
PREPARATORY REINFORCING SKIMCOAT:	Armourcoat Anticrack OR not required
LOCATION:	As drawing
HARDNESS:	Shore D Hardness test: 64, ASTM D3363 Pencil Harness: 5H+
RECYCLED CONTENT (MINIMUM):	38%
SYSTEM WEIGHT:	3.10-3.60 kg/m ²
EMBODIED CARBON:	EN15804 +A2: 0.34 Kg CO ₂ e
TECHNICAL CHARACTERISTICS, OTHER:	Mould and mildew resistance, to ASTM D3274: 10/10/10
COLOUR:	Insert colour selection
SEALER:	Aquawax as standard