



Document: 11007.6
Collection: 117: Advice Sheets
Modified: 11/01/2017 16:21
Created: 15/09/2016 17:27

Armourcoat Ltd
Morewood Close Sevenoaks Kent TN13 2HU
T: +44(0)1732 460 668 F: +44(0)1732 450 930
UK Company 1997888. VAT Reg: 445788013
www.armourcoat.com

Care & Maintenance Sheet 7 Ductal with Sealer 56

1 Maintenance

Depending on location, Ductal may require periodic dusting of the surface using a soft dry duster. The interval between removal of the dust will depend upon the local circumstances but should be carried out at least annually. A Vacuum cleaner with a brush attachment can also be used to remove the surface dust.

2 Cleaning Surface Dirt and Grime

The quickest and simplest way of removing small areas of surface grime and finger marks is to rub the affected area with a pencil eraser. The eraser will remove all but the most stubborn surface marks without affecting the surface in any way.

Larger areas will need to be cleaned with soapy water. First damp down the surface with just water but try not to disturb the dirt. When the surface is wet, then clean it with a mixture of water and mild detergent. Wetting the surface first will minimise the amount of dirty water absorbed into the surface.

Under no circumstances use acid-based cleaners for this process, as they may cause permanent damage.

3 Cleaning Scuff Marks

If the surface has been scuffed with a shoe or plastic item and cannot be removed with a pencil rubber, try the following method:

Take some masking tape and press it firmly onto the affected area and then pull directly off. Repeat this process 2 or 3 times or until the mark has been removed.

4 Stubborn Marks

If you are unable to remove any mark using a pencil rubber or masking tape, it may be necessary to lightly sand the surface in the affected area.

Sand the surface lightly with a fine grade sandpaper to achieve the required surface sheen level. Do not sand heavily in a small area as this may cause a dip and try to avoid sanding too far into the surface as this may expose the fibres. After sanding the surface will need to be re-sealed with Sealer 56. Contact Armourcoat on the number below to arrange for us to re-seal the surface.

5 Damaged Areas

Contact Armourcoat on the number below and arrange for us to do repairs.

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.